

Biomass Fly Ash in Concrete 1

Shuangzhen Wang, Todd Morris, Larry Baxter

Objective:

This investigation determines the effect of biomass fly ash and mingled biomass-coal ash in design mixes on concrete strength, flexure strength, freezing-thawing, setting time and rapid chloride permeability. The work intends to offer information to standardize biomass fly ash addition to concrete.


Elemental Analysis and LOI of Fly Ash and Cement

Elemental analysis and LOI of fly ash and cement						
(W %)	Class C	Class F	SW1	SW2	Wood	Cement
TOTAL	100.65	99.04	100.63	99.6	99.82	99.5
SiO ₂	37.26	54.91	52.16	53.02	48.94	21.5
Al ₂ O ₃	19.62	27.79	23.55	25.78	12.47	4.2
Fe ₂ O ₃	6.07	7.54	7.57	7.95	5.45	2.7
CaO	24.18	1.11	2.37	1.88	13.55	64.3
MgO	5.37	0.84	1.31	0.91	3.16	2.2
Na ₂ O	1.5	0.19	0.7	0.26	1.68	0.51
K ₂ O	0.43	2.4	4.01	2.14	3.37	
Cr ₂ O ₃	0.01	0.02	0.02	0.02	0.03	0
TiO ₂	1.52	1.63	1.45	1.65	0.78	0
MnO	0.01	0.02	0.04	0.02	0.12	0
P ₂ O ₅	1.2	0.28	1.04	1.1	0.95	0
SrO	0.3	0.1	0.13	0.2	0.06	0
BaO	0.66	0.12	0.18	0.38	0.07	0
SO ₃	1.82	0.37	2.25	1.23	1.3	2.6
LOI	0.7	1.72	3.85	3.06	7.89	1.3
Insoluble Residue	0	0	0	0	0	0.19

Project Investigation:


- water/ (cement + fly ash) ratio : 0.5
- 25% substitution of cement with fly ash and their combination
- air volume assumed as 5%
- Coarse aggregate sieved:1/2-1 in.:45%; 3/8-1/2in.:45%; No.4-3/8in. :9.5%; No.8-No.4: 0.50%
- 5 kinds of fly ashes and 2 of their combination are involved:
 1. class C
 2. class F
 3. wood (sieved with No 10 sieve)
 - 4 SW1 (co-fired 20%Switchgrass, 80% Galatia coal)
 5. SW2 (co-fired 10%Switchgrass, 90% Galatia coal)
 - 6.wood C (20% wood mingled with 80% class C)
 - 7 wood F (20% wood mingled with 80% class F)

Freezing-thawing Test




Error bars indicate a 95% confidence interval

Setting Time Test




Compressive Strength Test



Error bars indicate a 95% confidence interval

Flexure Strength Test (56th day)



Error bars indicate a 95% confidence interval

Rapid Chloride Permeability Test

